

www.TriCountyMetals.com



Make Your Next Roof Your Last

IIVFRVIFW

This panel is manufactured at our TCM plant.

Applications: Residential, Light Commerical, and Agricultural

Gauge: 26 Ga. and .032" Aluminum (inquire for special order)

Minimum Slope: 2 / 12

Panel Profile: 24" net coverage, 5 ribs 12" and 24" on-center, 3/8" high rib

Substrate: Galvalume® steel sheet, conforming to ASTM A792 Aluminum Sheet, 3105 H24, conforming to ASTM B209

Finish: Mill Finish AZ55 Acrylic Coated Galvalume®; 25 year limited warranty

TCM exclusive paint systems:

Core Defender Paint System[®] 40 / 30 year limited warranty. Coastal Defender Paint System[®] 25 year limited warranty.

COLORS

Please contact your salesperson for color availability.



12"-

BENEFITS

- Superior Enery Star service colors with stability proven through extensive Valspar® testing.
- - TCM exclusive Coastal Protector Series for projects with tough environmental locations.



3/8

Enhanced design from maximum leak resistance, low maintenance, long life.

STRIATED

FI A



Recommend Lifetime Screws for weather tight seals and a durable screw head.

FL Building Code approved to withstand winds up to 225 mph (when using HVHZ install method per product approval)



Florida Product Approval #4595.1, #4595.2, #36904 HZHZ*

*Note: HVHZ Designates this product approval includes HVHZ (High Velocity Hurricane Zone) product approval For other installation configurations, please inquire with your salesperson for site-specific accommodations.

Trenton 352-463-8400 Ocala 352-622-5500 Brooksville 352-587-8120 Jacksonville 904-490-6004

Live Oak 386-330-0101 Tallahassee 850-574-4001 DeLand 386-738-2579





