



## HIGH TEMPERATURE UNDERLAYMENT PROTECTION

### Premium Self-Adhering Waterproofing Protection

Ultra HT Wind & Water Seal™ is a 45 mil, self-adhering waterproofing underlayment composed of a non-slip, cross-laminated polymer film laminated to a High Temperature adhesive system.

Ultra HT is engineered for use as a whole roof underlayment for metal roofing systems. It can also be used in valleys, ridges, eaves and around chimneys for protection against wind-driven rain.





## **ULTRA HT WIND & WATER SEAL™ FEATURES:**

- + Composed of a non-slip, cross-laminated polymer film
- + Rated for High Temperature applications up to 250°F
- + Ideal for secondary water resistance
- + Self-sealing around fasteners
- + Minimum slope for installation is 2:12 pitch
- + Protects from leaks caused by wind-driven rain
- + May be left exposed for 90 days
- + 2-square roll
- + 10-year limited warranty
- + Made in the USA

**FLORIDA PRODUCT APPROVALS:** A current list Florida Product Approvals available on our website.  
For the most up-to-date Florida Product Approvals, please visit our  
website: [TriCountyMetals.com/florida-product-approvals/](http://TriCountyMetals.com/florida-product-approvals/)

For other installation configurations, please inquire with your salesperson for site-specific accommodations.

**Part of TCM's All Weather Defender System**