

UNDERLAYMENT



HYDRASHELL MAX

HYDRASHELL SUPREME SA



SYNTHETIC VS PEEL & STICK



Roofing Ventilation & Accessories

WHICH IS THE BEST CHOICE FOR YOUR PROJECT?

HYDRASHELL MAX SYNTHETIC ROOF UNDERLAYMENT

The reliable underlayment choice with a 30-year limited warranty.

- Won't wrinkle or absorb water
- Stays flexible in cold weather
- 25 times stronger than #15 felt
- 12 times stronger than #30 felt
- More coverage per roll
- Less weight per roll
- Requires fewer fasteners
- Cool Gray surface to reduce heat build-up
- 90-day UV exposure rating
- Class A fire rating
- Miami-Dade County Code approved
- Made in the USA

SPECS

Roll Dimensions: 40"/300'	Burst Strength: 160 psi
Permeability: 0.1 perms	Elongation: 20%
Water Transmission: Pass	Weight Per Square: 1.96 lbs
Tear Strength: 33 lbs MD/24 lbs CD	Nominal Thickness: 6.2 mils
Tensile Strength: 95 lbs MD/85 lbs CD	Temp. Range (Internal): -70° F to 240° F

HYDRASHELL SUPREME SA HT SELF-ADHERING SYNTHETIC

The BEST CHOICE in high-temp, easy-to-handle, self-adhering applications.

- Split-back release film peels off for easy installation
- Adheres to a variety of substrates
- Polymer-modified asphalt gives excellent pliability
- Exceptionally durable high-tensile/tear strengths
- Cool Gray surface to reduce heat build-up
- 90-day UV exposure rating
- 30-year limited warranty
- Made in the USA

SPECS

Boxed packaging
 Roll Dimensions: 36"/67'
 Roll Weight: 55 lbs
 Cartons Per Pallet: 30
 Permeability (ASTM E96): .067 perms
 Nail Sealability (D1970): Pass

FL PRODUCT APPROVALS



Adhesion To Plywood @ 75° F (D903): >12 lbs/ft
 Adhesion To Plywood @ 40° F (D903): >2 lbs/ft
 Mill Thickness (ASTM D5147): 44
 Flexibility At -20° F (D1970): Pass
 High Temperature Rating: 240° F



TriCountyMetals.com
 SERVING FLORIDA & GEORGIA

LOCATIONS

TRENTON	TALLAHASSEE
OCALA	DELAND
BROOKSVILLE	WINTER HAVEN
JACKSONVILLE	OKEECHOBEE
LIVE OAK	

